



EVCO4 HC BW

VERTICAL COOLER

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

Energy efficient HC unit, designed for checkout locations with special steel top, ideal for small footprint areas.



KEY FEATURES



- **Eco-Friendly Refrigerant**
Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.



- **Electronic Temperature Controller**
Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



- **High Power Reliable Refrigeration System**
Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.



- **Newly Designed Condenser**
New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



- **Standard LED Lighting System**
Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.






- **Spark-Free Refrigeration Components**
All Reach-In models will have spark free refrigeration components for optimal safety, per UL requirements.



ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

PRODUCT VIEWS


TOP VIEW



ADDITIONAL FEATURES



> Manual Lock - External lock available



> Gravity kit - Display technology beverage Visi-Slide



> Casters and legs available



> Left side Hinge

Customer service and warranty

Three year limited warranty, includes parts and labor.

An additional two year warranty is issued on the compressor (USA & Canada only).

Operators must follow installation and operational guidelines per Imbera Users Manual.

Each cooler must be connected directly to a single power supply, otherwise warranty will be voided.

Customer service: 866.548.5770

TECHNICAL SPECIFICATIONS

Exterior Dimensions

H: 33 7/10" 86 cm
W: 21" 53 cm
D: 23 2/5" 59 cm

Interior Dimensions

H: 28 3/5" 73 cm
W: 18 1/10" 46 cm
D: 17 7/10" 45 cm

Usable Interior Capacity

H: 26 3/5" 68 cm
W: 17 3/10" 44 cm
D: 12 1/10" 31 cm

Usable Volume

3.24 ft³
91.62 lts

Doors	Door construction	Shelves	Shelves Size
1	Plastic frame	2	W: 17 3/10" 44 cm D: 12 1/10" 31 cm

External Material Pre-painted steel

Internal Material Pre-painted steel

REFRIGERATION PERFORMANCE DATA

Refrigerant

R600 1.1 Oz (0.03 kg)

Energy Consumption

0.780 kWh/24h

Compressor Power

1/12 HP

Condenser

Finless (low maintenance)

Thermostat setting default

Cut-Out
32°F [0°C]

Cut-In
44.6°F [7°C]

ELECTRICAL DATA

Power supply

115V/60 Hz

AMPS

2.0 A

Lighting

331.1 Lux Output
4 modules
8 LED per module

Plug Type

NEMA 5-15P

Controller

ETC1H

Cord length

128" [3270 mm]

LOGISTIC DATA

Trailer Loads

53': 160

Unit weight with packaging

124.45 lb 52.1 kg

without packaging

114.86 lb 56.45 kg

Dimensions w/packaging

H: 34 3/10" 87 cm

W: 23 7/10" 60 cm

D: 26 1/5" 67 cm

*Energy consumption based on ANSI/ASHRAE Standard 72-2005

*BMAD System (Low maintenance high performance)

*Dimensions rounded up to the nearest inch or centimeter

*Specifications subject to change without notice

*H: Height, W: Width, D: Depth

09/07/2021