



VR04 HC BW

VERTICAL COOLER

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

Energy efficient, eco-friendly HC countertop unit specially designed for checkout locations and small footprint areas.



KEY FEATURES



- **Eco-Friendly Refrigerant**
Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.




- **Electronic Temperature Controller**
Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



- **High Power Reliable Refrigeration System**
Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.



- **Newly Designed Condenser**
New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



- **Standard LED Lighting System**
Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.



- **Spark-Free Refrigeration Components**
All Reach-In models will have spark free refrigeration components for optimal safety, per UL requirements.






DOE

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

PRODUCT VIEWS

TOP VIEW



TECHNICAL SPECIFICATIONS

Exterior Dimensions

H:	38 1/4"	97 cm
W:	18 7/8"	48 cm
D:	20 1/4"	64 cm

Interior Dimensions

H:	24 3/4"	63 cm
W:	15 7/8"	40 cm
D:	16 3/4"	42 cm

Usable Interior Capacity

H:	23 1/4"	59 cm
W:	14 3/4"	37 cm
D:	14 1/8"	36 cm

Usable Volume

3.9 ft ³
111 lts

Doors	Door construction	Shelves	Shelves Size
1	V7 Plastic frame	3	W: 15 1/4" 39 cm D: 14 5/8" 37 cm

External Material Pre-painted steel

Internal Material Pre-painted steel

REFRIGERATION PERFORMANCE DATA

Refrigerant

R290 3.2 Oz (0.09 kg)

Energy Consumption

0.950 kWh/24h

Compressor Power

1/6 HP

Condenser

Finless (low maintenance)

Thermostat setting default

Cut-Out
32°F [0°C]

Cut-In
44.6°F [7°C]

ELECTRICAL DATA

Power supply

115V/60 Hz

AMPS

3.0 A

Lighting

255.2 Lux Output
2 modules
6 LED per module

Plug Type

NEMA 5-15P

Controller

ETC1H

Cord length

118" [3000 mm]

LOGISTIC DATA

Trailer Loads

53': 232

Unit weight with packaging

95.9 lb 43.5 kg

without packaging

89.3 lb 40.5 kg

Dimensions w/packaging

H: 38 5/8" 98 cm

W: 20 1/2" 52 cm

D: 26 3/4" 68 cm

Customer service and warranty

Three year limited warranty, includes parts and labor.

An additional two year warranty is issued on the compressor (USA & Canada only).

Operators must follow installation and operational guidelines per Imbera Users Manual.

Each cooler must be connected directly to a single power supply, otherwise warranty will be voided.

Customer service: 866.548.5770

*Energy consumption based on ANSI/ASHRAE Standard 72-2005

*PA System (Active Sides)

*Dimensions rounded up to the nearest inch or centimeter

*Specifications subject to change without notice

*H: Height, W: Width, D: Depth

07/09/2021