



# VR06 HC BW

## VERTICAL COOLER

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

Energy efficient, eco-friendly HC countertop unit with low charge, spark-free components, and the lowest utility costs in its category.



### KEY FEATURES



- **Eco-Friendly Refrigerant**  
Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.




- **Electronic Temperature Controller**  
Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



- **High Power Reliable Refrigeration System**  
Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.



- **Newly Designed Condenser**  
New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



- **Standard LED Lighting System**  
Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.



- **Spark-Free Refrigeration Components**  
All Reach-In models will have spark free refrigeration components for optimal safety, per UL requirements.






DOE

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

### PRODUCT VIEWS


#### TOP VIEW



### ADDITIONAL FEATURES



> Manual lock - external lock available



> Display technology beverage Visi-Slide



> Casters and legs available



> Price kit available for shelf display

#### Customer service and warranty

Three year limited warranty, includes parts and labor.

An additional two year warranty is issued on the compressor (USA & Canada only).

Operators must follow installation and operational guidelines per Imbera Users Manual.

Each cooler must be connected directly to a single power supply, otherwise warranty will be voided.

Customer service: 866.548.5770

### TECHNICAL SPECIFICATIONS

#### Exterior Dimensions

H: 36 4/5" 93 cm  
W: 21 1/10" 54 cm  
D: 26 1/10" 66 cm

#### Interior Dimensions

H: 31 7/10" 80 cm  
W: 17 9/10" 46 cm  
D: 21 4/5" 55 cm

#### Usable Interior Capacity

H: 31 1/5" 79 cm  
W: 16 7/10" 42 cm  
D: 16 2/5" 42 cm

#### Usable Volume

5.1 ft<sup>3</sup>  
144.4 lts

Doors	Door construction	Shelves	Shelves Size
1	NGD Plastic frame	3	W: 17 1/10" 44 cm D: 17 1/10" 44 cm

**External Material** Pre-painted steel

**Internal Material** Pre-painted steel

### REFRIGERATION PERFORMANCE DATA

#### Refrigerant

R600a 1.2 Oz (0.034 kg)

#### Energy Consumption

0.910 kWh/24h

#### Compressor Power

1/8 HP

#### Condenser

Finless (low maintenance)

#### Thermostat setting default

#### Cut-Out

32°F (0°C)

#### Cut-In

44.6°F (7°C)

### ELECTRICAL DATA

#### Power supply

115V/60 Hz

#### AMPS

2.2 A

#### Lighting

219.6 Lux Output  
4 modules  
8 LED per module

#### Plug Type

NEMA 5-15P

#### Controller

ETC1H

#### Cord length

118" (3000 mm)

### LOGISTIC DATA

#### Trailer Loads

53': 160

#### Unit weight with packaging

119.0 lb 54.0 kg

without packaging  
124.6 lb 56.5 kg

#### Dimensions w/packaging

H: 37 3/5" 96 cm

W: 22 1/2" 57 cm

D: 29 2/5" 75 cm

\*Energy consumption based on ANSI/ASHRAE Standard 72-2005

\*BMAD System (Low maintenance high performance)

\*Dimensions rounded up to the nearest inch or centimeter

\*Specifications subject to change without notice

\*H: Height, W: Width, D: Depth

07/09/2021