



VR08 HC BW

VERTICAL COOLER

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

Energy efficient, eco-friendly HC refrigerant with low charge, spark-free components, and the lowest utility costs in its category.



KEY FEATURES



- **Eco-Friendly Refrigerant**
Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.



- **Electronic Temperature Controller**
Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



- **High Power Reliable Refrigeration System**
Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.



- **Newly Designed Condenser**
New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



- **Standard LED Lighting System**
Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.






- **Spark-Free Refrigeration Components**
All Reach-In models will have spark free refrigeration components for optimal safety, per UL requirements.



ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

PRODUCT VIEWS

TOP VIEW



ADDITIONAL FEATURES



> Manual lock - external lock available



> Display technology beverage Visi-Slide



> Casters and legs available



> Price kit available for shelf display

Customer service and warranty

Three year limited warranty, includes parts and labor.

An additional two year warranty is issued on the compressor (USA & Canada only).

Operators must follow installation and operational guidelines per Imbera Users Manual.

Each cooler must be connected directly to a single power supply, otherwise warranty will be voided.

Customer service: 866.548.5770

TECHNICAL SPECIFICATIONS

Exterior Dimensions

H: 72 1/2" 184 cm
W: 20 1/4" 51 cm
D: 22 5/8" 58 cm

Interior Dimensions

H: 52 7/8" 135 cm
W: 15 7/8" 40 cm
D: 16 3/4" 42 cm

Usable Interior Capacity

H: 45 1/2" 116 cm
W: 14 5/8" 37 cm
D: 14 1/8" 36 cm

Usable Volume

7.7 ft³
217.8 lts

Doors	Door construction	Shelves	Shelves Size
1	V7 Plastic frame	5	W: 15 1/8" 38 cm D: 14 5/8" 37 cm

External Material Pre-painted steel

Internal Material Pre-painted steel

REFRIGERATION PERFORMANCE DATA

Refrigerant

R600a 1.6 Oz (0.045 kg)

Energy Consumption

1.160 kWh/24h

Compressor Power

1/8 HP

Condenser

Finless (low maintenance)

Thermostat setting default

Cut-Out
32°F (0°C)

Cut-In
44.6°F (7°C)

ELECTRICAL DATA

Power supply

115V/60 Hz

AMPS

1.8 A

Lighting

394.1 Lux Output
7 modules
8 LED per module

Plug Type

NEMA 5-15P

Controller

ETC1H

Cord length

118" (3000 mm)

LOGISTIC DATA

Trailer Loads

53': 100

Unit weight with packaging

182.0 lb 82.6 kg

without packaging

177.8 lb 80.7 kg

Dimensions w/packaging

H: 74 2/3" 190 cm

W: 19 2/3" 50 cm

D: 21" 53 cm

*Energy consumption based on ANSI/ASHRAE Standard 72-2005

*BMAD System (Low maintenance high performance)

*Dimensions rounded up to the nearest inch or centimeter

*Specifications subject to change without notice

*H: Height, W: Width, D: Depth

07/09/2021