



VR10 HC BW

VERTICAL COOLER

ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

Energy efficient, eco-friendly HC refrigerant with low charge, spark-free components, and the lowest utility costs in its category.



KEY FEATURES



- **Eco-Friendly Refrigerant**
Environmentally friendly hydrocarbon refrigerant has low Global Warming Potential (GWP). Meets all USA & California refrigerant & energy standards.



- **Electronic Temperature Controller**
Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



- **High Power Reliable Refrigeration System**
Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining colder temperatures for food preservation.



- **Newly Designed Condenser**
New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



- **Standard LED Lighting System**
Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.





- **Spark-Free Refrigeration Components**
All Reach-In models will have spark free refrigeration components for optimal safety, per UL requirements.



ESTABLISHING A **NEW STANDARD** IN THE FOODSERVICE INDUSTRY.

PRODUCT VIEWS


TOP VIEW



ADDITIONAL FEATURES



> Manual lock - external lock available



> Gravity kit - Display technology beverage Visi-Slide



> Casters and legs available



> Price kit available for shelf display

Customer service and warranty

Three year limited warranty, includes parts and labor.

An additional two year warranty is issued on the compressor (USA & Canada only).

Operators must follow installation and operational guidelines per Imbera Users Manual.

Each cooler must be connected directly to a single power supply, otherwise warranty will be voided.

Customer service: 866.548.5770

TECHNICAL SPECIFICATIONS

Exterior Dimensions

H: 53 9/10" 137 cm
W: 24 4/5" 63 cm
D: 22 7/10" 58 cm

Interior Dimensions

H: 40 3/5" 103 cm
W: 21 9/10" 56 cm
D: 18 1/2" 47 cm

Usable Interior Capacity

H: 35 1/5" 89 cm
W: 20 3/10" 52 cm
D: 16 7/10" 43 cm

Usable Volume

9.43 ft³
267 lts

Doors	Door construction	Shelves	Shelves Size
1	V7 Plastic frame	3	W: 20 9/10" 53 cm D: 17 3/10" 44 cm

External Material Pre-painted steel

Internal Material Pre-painted steel

REFRIGERATION PERFORMANCE DATA

Refrigerant

R290 1.7 Oz (0.047 kg)

Energy Consumption

1.250 kWh/24h

Compressor Power

1/10 HP

Condenser

Finless (low maintenance)

Thermostat setting default

Cut-Out
32°F [0°C]

Cut-In
44.6°F [7°C]

ELECTRICAL DATA

Power supply

115V/60 Hz

AMPS

3.2 A

Lighting

315 Lux Output
5 modules
8 LED per module

Plug Type

NEMA 5-15P

Controller

ETC1H

Cord length

118" [3000 mm]

LOGISTIC DATA

Trailer Loads

53': 80

Unit weight with packaging

176.1 lb 79.9 kg

without packaging

171.1 lb 77.6 kg

Dimensions w/packaging

H: 57 9/10" 147 cm

W: 26 2/5" 67 cm

D: 23 2/5" 60 cm

*Energy consumption based on ANSI/ASHRAE Standard 72-2005

*BMAD System (Low maintenance high performance)

*Dimensions rounded up to the nearest inch or centimeter

*Specifications subject to change without notice

*H: Height, W: Width, D: Depth

07/09/2021